

DIN Rail



Dycon DIN Rail Mounted Power Supply Modules and Options



Illustration shows a Dycon D1543 13.8VDC 3A Power supply fitted into a Medium Size DIN cradle

- Standard DIN Rail fixings top head and G profile
- Suitable for NS32-G & N35 7.5mm/15mm
- With or without battery charging
- Fully integrated options

Increasingly, throughout the world, large buildings and construction sites concentrate on low-voltage power distribution and services into DIN rail cabinets, rather than having many separate boxes screwed to walls. To meet this demand, Dycon has a wide range of advanced technology, switched-mode power supply units mounted into DIN rail cradles and two fully integrated versions that do not need a separate cradle. These power supply units can provide output voltages of 12VDC and 24VDC for non-battery backed applications or 13.8VDC and 27.6VDC, where standby-battery charging capability is required. Output voltages of between 1 Amp and 5 Amps make them ideally suited for security, IOT, access control and communication & building management, system applications, as well as anything else that requires reliable power. Installation is simple, no need to drill holes or screw anything in place, simply clip the whole unit onto the DIN rail and connect the cables to the marked terminals.

DIN Rail Power Supply Options

A range of switched-mode power supply units and accessories mounted in Dycon DIN Rail cradles

Dycon DIN Rail Mounted Power Supplies & Accessories

Power Supply Part No.	Power Supply Description	DIN Cradle fitted
D1503-D	Ultra-Low Emission 13.8VDC 3A with battery charging	DINRAILKITSM
D1541-D	13.8VDC 1A multi-indicator with battery charging	DINRAILKITSM
D1542-D	13.8VDC 2A multi-indicator with battery charging	DINRAILKITSM
D1543-D	13.8VDC 3A multi-indicator with battery charging	DINRAILKITSM
D1555-D	13.8VDC 5A "Smart" unit with battery charging, 1 fault output and 3 led indicators	DINRAILKITLRG
D2401-D	24VDC 1A without battery charging	DINRAILKITSM
D2413-D	27.6VDC 3A with battery charging	DINRAILKITLRG
D2441-D	27.6VDC 1A 'Smart' unit with battery charging, 3 fault outputs, power on/off input and 4 led indicators	DINRAILKITLRG
D15X8-D-500	8-way glass-fused output splitter with 500 mA Fuses	DINRAILSPLITTER
D15X8-D-1	8-way glass-fused output splitter with 1 A Fuses	DINRAILSPLITTER
DR-60-12	110VAC -230VAC input - 12VDC 2.5A output	Integral DIN rail mount
DR-60-24	110VAC -230VAC input - 24VDC 4.4A output	Integral DIN rail mount

Product Part Numbers	Description	Size incl. PSU L x W x H
DINRAILKITSM	Medium DIN Cradle	134mm x 90mm x 70mm
DINRAILKITLRG	Large DIN Cradle	143mm x 125mm x 74mm
DINRAILSPLITTER	Splitter Profile DIN Cradle	53mm x 125mm x 36mm
DR-60-12	Integrated DIN rail mounted 12VDC power supply	78mm x 93mm x 56mm
DR -60-24	Integrated DIN rail mounted 24VDC power supply	78mm x 93mm x 56mm
DIN-Custom-xxx	Top Head DIN rail TS35/7.5 for Dycon housings	Length depending on housing x 35 x 7.5mm

The DIN Cradles can be supplied separately for retrofitting or refitting to existing Dycon power modules. DIN rail cradles are made of PVC, inflammability class according to UL94 V0. Colour: Green.

Dycon Power Solutions Ltd

Unit A, Cwm Cynon Business Park, Mountain Ash,
CF45 4ER, United Kingdom.

For more information about the Dycon products:

website: www.dyconpower.com

email: sales@dyconpower.com

Or to discuss your specific needs:

+44 (0)1443 471 900



Dycon leads the security and associated power supply markets, with UK design and manufacture of advanced power products, engineered to provide high quality, cost-effective solutions to meet current regulations and the specific needs of system integrators and end-users.

Din-Rail Cradles data sheet 07052020 V10