

D1551 & D1553



Multi-Indicator, Switched-Mode 1A and 3Amp Power Supplies



Illustration shows a D1553-X8-CDIN 3A unit with an optional D15X8 splitter, a DIN-Rail and feather-trunking

- 1A or 3A, output versions
- 13.7VDC 300mA battery charging current
- Protection against electrical spikes, battery deep-discharge & over voltage
- Opto relay fault output
- Switchable ON/OFF input
- Self-resetting PTC fuse
- 3 x LED Indicators can show 14 separate fault/status conditions
- Extensive range of steel and IP65 plastic housings

These Dycon units are switched-mode power supplies with normally closed (NC) volt-free, opto-relay outputs, for remotely signalling the status and serviceability of units. The outputs can be used to indicate problems either locally or remotely via a suitable signalling device. Specially designed for access control applications using Dycon's unique protective technology, these units' feature a switchable ON/OFF output capable of switching highly inductive loads (door strikes and locks). Also removing the chance of inductive kickback blowing a fuse and causing a door to remain closed or open, a frequent cause of personnel delays and expensive engineer call outs. This output is ideal for interfacing with fire alarm systems, where a single command from a fire panel can release all the doors, equally, it can be used with timers to activate to turn on or off an access system at predetermined times. These units feature intelligent and capacitive load switching surge protection and snubbing and all include a jumper for simple selection of inverted or normal power switching input operation. Optional output splitters are also available, connected to the power output, a D15X8-500mA provides up to 8 x individually-fused 500mA outputs, the D15X8-1A provides 8 x individually-fused 1A outputs, both with LED indicators. The DFX4-OP has 4 x self-resetting electronically fused outputs and LED indicators.

Access Control Power Solutions

12VDC Switched-Mode Solutions

Ideal for Access Control Systems

Power Supply	Type A, Ungraded, Environmental Class 2
Voltage Input	195VAC -265VAC @ 50-60Hz
AC Input Current	D1551-200mA; D1553-400mA;
AC Input Fuse	D1551-1A; D1553-3A;
Output Voltage with AC Power	Maximum 13.9VDC, minimum 13.5VDC
Output Ripple	< 0.25V peak-to-peak at full rated output
Maximum Output Current at Full Load	D1551-1A : D1553-3A;
Battery Charging Current and Voltage	300mA at 13.7VDC float charge voltage
Minimum Standby Output Voltage	9.6VDC
Maximum Power Input at Full Load	D1551-16W; D1553-47W;
Fault Opto-Relay Rating	60V @ 100mA, 14ohms closed
Efficiency	>85% @ 5A load
Maximum Over-Voltage Cut-Out	14.4VDC ±3%
Low Battery Fault	11VDC ±3%
Low-Voltage Power Output Fault	12.3VDC ±3%
Battery Deep Discharge Voltage Limit	10VDC ±3%
Automatic Reset Time*	10ms to 18s (Depending on type and duration of fault)
Operating Temperature Range	-10°C to +40°C
Humidity	95% non-condensing

1A version D1551	3A version D1553	Housing Type	Suitable batteries	Dimensions H x W X D (mm)	Weight (Kg)
D1551-A	D1553-A	Small, Steel A size	1 x 7/8Ah	235 x 170 x 85	1.35
D1551-B	D1553-B	Medium, steel B size	2 x 7/8Ah	260 x 320 x 90	2.15
D1551-XB	D1553-B	Clam-shell lid, Steel XB size	2 x 7/8Ah or 2 x 17Ah	295 x 425 x 90	2.45
D1551-XLB	D1553-XLB	Standard, steel XLB size	2 x 7/8Ah or 2 x 17Ah	295 x 425 x 90	2.45
D1551-XLBD	D1553-XLBD	Extra-deep, steel XLBD size	Up to 4 x 17Ah	295 x 490 x 165	4.65
D1551-C	D1553-C	Large, steel C size	2 x 7/8Ah or 2 x 17Ah	345 x 430 x 90	3.55
D1551-E	D1553-E	Very-large, steel E size	2 x 7/8Ah or 2 x 17Ah	405 x 500 x 90	6.05
D1551-G	D1553-G	Extra-large G-size	2 x 24Ah or up to 4 x 17Ah	690 x 455 x 165	8.75
D1551-W	D1553-W	IP65, ABS plastic W-size	1 x 2.1Ah or 1 x 7/8Ah	245 x 195 x 90	1.70
D1551-P	D1553-P	PCB-only version	Depends on housing	D1551= 93 x 131 x 42 D1553= 93 x 135 x 42 (This 42mm increases to 46mm when a stand-off is used)	0.13 0.16
Dycon Accessories for use with both D1551 & D1553, these can be specified to be factory-fitted into a specific PSU housing					
D15X8-500mA	8-way output splitter (8 x 500mA glass fuses)			49 x 108 x 17	0.70
D15X8-1A	8-way output splitter (8 x 1A glass fuses)			49 x 108 x 17	0.70
D15X4-BNP	4-way output splitter with 4 x BNC sockets & video loop-through			71 x 128 x 15	0.80
DFX4-OP	4-way output splitter with 4 x self-resetting PET fuses			40 x 60 x 19	0.20
DFR-1-12	12VDC universal output relay module			40 x 16 x 19	0.26

Dycon Power Solutions Ltd

Unit A, Cwm Cynon Business Park, Mountain Ash
CF45 4ER, United Kingdom.

For more information about the Dycon products:

website: www.dyconpower.com

email: sales@dyconpower.com

Or to discuss your specific needs:

+44 (0)1443 471 900

Dycon leads the security and associated power supply markets, with UK design and manufacture of advanced power products; engineered to provide high quality, cost-effective solutions to meet current regulations and the specific needs of system integrators and end-users.

Designed and manufactured in the UK

D1551_D1553 data sheet 08092023v2